



PH: (718)417-6464 * (800)403-0011 / FX: (718)497-4845 * (800)952-8281

LUBENET EP SAE 90 GEAR OIL

PRODUCT SPECIFICATIONS & TECHNICAL DATA

LUBENET MULTI-PURPOSE GEAR LUBRICANTS are blended with high quality base stocks and additives to inhibit oil oxidation, protect against corrosion, and provide excellent rust and foam protection. **LUBENET MULTI-PURPOSE GEAR LUBRICANTS** provide continual protection to gears during periods of high temperature operation, and are approved for MACK GO-A. **LUBENET MULTI-PURPOSE GEAR LUBRICANTS** are extreme pressure, heavy duty lubricants that contain a sulfur phosphorus additive package, developed to meet rigorous service demands and provide excellent gear and bearing protection. **LUBENET MULTI-PURPOSE GEAR LUBRICANTS** are compatible with most other gear lubricants. Because these lubricants are multi-purpose, the worry of misapplication is minimized, and inventory control is simplified.

APPLICATIONS: **LUBENET MULTI-PURPOSE GEAR LUBRICANTS** are recommended for construction equipment, truck and bus fleets, farm machinery and passenger cars. They can be used for service fill, make-up, or top-off of manual transmissions, differential, real axles, manual steering gears, final drives and universal joints.

TYPICAL ANALYSIS

	EP 90W
Gravity API	26.5
Viscosity Index	110
Flash Point °F	425
Pour Point °F	0
Viscosity SUS @ 100° F	1175
Viscosity SUS @ 210° F	96.1
ISO VG	220
AGMA	5 EP

The above analyses are typical inspections only and the finished product may vary from batch to batch.