

PH: (718) 417-6464 * (800) 403-0011 / FX: (718) 497-4845 * (800) 952-8281

LUBENET EP 80W-90 GEAR OIL

PRODUCT SPECIFICATIONS & TECHNICAL DATA

LUBENET EP GEAR OIL are multi-purpose, extreme pressure gear oils that meet the requirements of API (American Petroleum Institute) gear oil classification GL-5, and Military Specification, MIL-PRF-2105E. **LUBENET EP GEAR OIL** are multi-purpose gear oils that are formulated with high quality base oils, and additives to provide excellent load carrying ability, EP properties, wear resistance, oxidation stability, anti-rust and anti-corrosion qualities, and anti-foam protection. **LUBENET EP GEAR OIL** are recommended for make-up and complete refill of most passenger car and light truck conventional differentials, transmission, and steering gears. **LUBENET EP GEAR OIL** are multi-purpose, extreme pressure gear oils that are now considered thermally stable and will provide transmission, differential and other application protection beyond that specified for the current MIL-PRF-2105E, API GL-5 requirements. This thermal stability extends oil service life, and reduces critical component wear.

APPLICATIONS:

Pour Point °C / °F

Viscosity SUS @ 100° F

Viscosity SUS @ 210° F

| *MIL-PRF-2105E | *API Service GL-5 | | *Eaton |
|---|--------------------------|-------------------|-------------|
| *API MT-1 (80W90) | | *American Motors | *Nissan |
| *Mack Truck GO-J | *Chr | ysler Corporation | *Navistar |
| *BMW | *Clark Equipment Company | | |
| *Dodge | | | · – |
| *General Motors | *Johr | n Deere Company | *Volkswagen |
| *Rockwell International *Ford Motor Company | | | |
| *Euclid | *Ren | ault | |
| TYPICAL ANALYSIS | | | |
| | | | |
| EP 80W-90 | | | |
| Gravity API | | 27.6 | |
| Viscosity Index | 104 | | |
| Flash Point °C / °F | | 210/392 | |

-27/-16

771

78.9

Viscosity Cst @ 40° C 147.1 Viscosity Cst @ 100° C 14.8 Specific Gravity @ 60° F 8894

The above analyses are typical inspections only and the finished product may vary from batch to batch.