



Universal (Global) Yellow -34 Extended Life ANTI-FREEZE / COOLANT

This anti-freeze is specifically formulated and recommended for all cars worldwide and light duty trucks with conventional, aluminum and brass radiators. This anti-freeze meets factory requirements for GM, Chrysler, Ford, European and Asian cars, regardless of year, make or model and original anti-freeze color.

- Unsurpassed freeze-up and boil-over protection
- Extended rust and corrosion protection
- Silicate & Phosphate Free
- Outstanding high temperature aluminum protection
- Excellent heat transfer properties
- Extends water pump life
- Compatible with DEXCOOL™ Extended Life Anti-Freeze / Coolant
- Compatible with all conventional & extended life anti-freeze
- 5 year / 150,000 mile protection when cooling system is completely flushed and filled with Magic Color™ Extended Life Anti-Freeze / Coolant
- Can be used to top-off any color of automotive anti-freeze including green, yellow, orange, red, blue and pink)
- Amber color will not change the current anti-freeze color when used for topping-off
- Meets ASTM D-3306 and ASTM D-4340

CHEMICAL PROPERTIES

PROPERTIES METHOD	TYPICAL VALUES	ASTM TEST
SPECIFIC GRAVITY AT 60 / 60° F	1.120-1.130	D 1122
BOILING POINT REFLUX	325° F MIN (with 15# pressure cap)	D 1120
FOAM TEST	50 ml / 3 SEC MAX	D 1881
pH 50% VOLUME SOLUTION	7.5 MIN-10.0 MAX	D 1287
FLASH POINT COC	250° F MIN	D 92
TOTAL WATER, Wt %	5% MAX	D 1123
TOTAL GLYCOLS, Wt %	95% MIN	E 202
COLOR	YELLOW	

AUTOMOTIVE ANTI-FREEZE SPECS

Recommended for Automobiles with the following Anti-Freeze Specifications:

* ANFOR R 15-601	* GM 1825M
* BS 6580 (British Standard)	* GM 6277M (Dex-Cool® Spec)*
* Chrysler MS7170	* JASO M325 (Japan)
Chrysler MS9769	* JIS K 2234 (Japan)
* Ford ESE-M97B44-A	* SAE J1034
* Ford WSS-M97B44-D	* Mercedes Benz DBL*
* Ford WSS-M97B51-A1	7700
FVV HEFT R443 (Germany)	