

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Gear Oil 85W-140

Product Code: 803

Chemical Name: Petroleum Oil; Lube Oil, Petroleum hydrocarbon, Lubricant

Chemical Family: Gear Oil

Recommended Use: Gear Oil

Manufacturer: LUBENET LLC

126 SCOTT AVE

BROOKLYN NY 11237

2. HAZARD IDENTIFICATION

This material is not considered hazardous by OSHA Hazard Communication Standard 29 CFR 1910.1200

Classification of the substance or mixture

Not Classified.

GHS label elements

Signal word No Signal Word Not Hazardous

Hazard Statements No known significant effects or critical hazards

Precautionary statements

General Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention P273 Avoid release into the environment.

Response P391 Collect Spillage

Storage Not Applicable

Disposal P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Other Hazards

The mixture consists of substances capable of producing an aspiration hazard. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure, and even death.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Wt. Percent	Component	CAS#
0 - 96.2	Highly refined petroleum base oil	Various*
1.2 – 3.0	Mineral Oil	Mixture
0.40-0.80	Zinc dialkyl dithiophosphate	68649-42-3

Component Related Regulatory Information

*Highly refined petroleum lubricating oil contains one or more CAS numbers listed as follows:

64741-88-4, 64742-52-5, 64742-54-7, 64742-55-8, 64742-65-0, 64742-57-0, 64742-01-4, 64742-62-7, 72623-83-7

4. FIRST AID MEASURES

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Eyes: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention.

Skin: In case of contact, immediately flush skin with plenty of water or at least 15 minutes while removing

: ~~88~~minated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops or persists.

Ingestion: DO NOT INDUCE VOMITING. If conscious, rinse out mouth with water. Call POISON CENTER or seek medical attention immediately.

Symptoms (Acute and delayed):

General: No known significant effects or critical hazards.

Inhalation: Over exposure may be irritating to the respiratory system.

Skin: Repeated or prolonged skin contact may cause irritation.

Eyes: Direct contact with the eyes is likely irritating.

Ingestion: May be fatal if swallowed and enters airways.

Chronic Symptoms: No know significant effects or critical hazards.

Note to Physicians: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. FIRE FIGHTING MEASURES

FLASHPOINT (METHOD): 329°F (165°C) Minimum COC

FLAMMABLE LIMITS: Not established

AUTO-IGNITION TEMP: Not available

CONDITIONS OF FLAMMABILITY: Can be made to burn. Does not ignite readily.

EXTINGUISHING MEDIA: Water spray, dry chemical, carbon dioxide (CO₂), regular foam.

HAZARDOUS COMBUSTION PRODUCTS: Decomposition and combustion material may be toxic. Burning may product sulfur oxides, aldehydes, ketones, carbon monoxide and unidentified organic compounds.

HAZARD RATING

0= LEAST

1=SLIGHT

2=MODERATE

3=HIGH

4=EXTREME

NEPA 704 HAZARD IDENTIFIATION

HEALTH HAZARD (BLUE)

1

FIRE HAZARD (RED)

1

REACTIVITY (YELLOW)

0

SPECIFIC HAZARD (WHITE)

FIRE FIGHTING INSTRUCTIONS: Keep storage containers cool with water spray. A positive-pressure, self-contained breathing apparatus (SCBA) and full- body protective equipment are required for fire emergencies.

FIRE AND EXPLOSION HAZARDS: Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Products are not sensitive to mechanical impact or static discharge.

6. ACCIDENTAL RELEASE MEASURES

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **Section 8: EXPOSURE**

CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean spark-proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

7. HANDLING AND STORAGE

HANDLING: Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. This product has a low vapor pressure and is not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating, this product, do not breathe vapor or mist. Use in a well-ventilated area. Avoid contact with eyes, skin clothing and shoes.

Keep container tightly closed when not in use and ~~Page~~ 3 of 6 transport. Store containers in a cool, dry place. Do not pressurize, cut weld, braze, solder, drill or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain residue and can be dangerous.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES:

COMPONENT EXPOSURE LIMITS

Highly Refined Petroleum Lubricating Oil

ACGIH: 5mg/m³ TWA (sampled by method that does not collect vapor) (related to Oil mist, mineral)
10 mg/m³ STEL (sampled by method that does not collect vapor) (related to Oil mist, mineral)
OSHA Final: 5 mg/m³ TWA (related to Oil mist, mineral)
OSHA Vacated: 5mg/m³ TWA (related to Oil Mist, mineral)
NIOSH: 5mg/m³ TWA (related to Oil Mist, mineral)
10mg/m³ STEL (related to Oil mist, mineral)

Mineral Oil

ACGIH: 5mg/m³ TWA (sampled by method that does not collect vapor) (related to Oil mist, mineral)
10 mg/m³ STEL (sampled by method that does not collect vapor) (related to Oil mist, mineral)
OSHA Final: 5mg/m³ TWA (related to Oil Mist, mineral)

ENGINEERING CONTROLS:

VENTILATION: Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT —

EYE: Splash proof chemical goggles recommended to protect against splash of product.

RESPIRATORY: No respiratory protection is normally required. Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

SKIN: Where skin contact is likely, wear neoprene, nitrile or equivalent protective gloves; use of natural rubber or equivalent gloves is not recommended. When product is heated and skin contact is likely, wear heat-insulating gloves, boots and other protective clothing.

PERSONAL HYGIENE: Use good personal hygiene. Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard leather articles, such as shoes, saturated with these products.

OTHER: Where spills and splashes are likely, facilities storing or using these products should be equipped with emergency eyewash and shower, both equipped with clean water, in the immediate work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/ODOR: AMBER FLUID/PETROLEUM ODOR.

VAPOR PRESSURE: LESS THAN 0.1(mm Hg @ 68°F 20°C)

MOLECULAR WEIGHT: N/D

INITIAL BOILD POINT: 501°F (260.56°C) (MINIMUM)

SOLUBILITY IN WATER: INSOLUABLE

EVAPORATION RATE: N/D

SPECIFIC GRAVITY: 0.86 (WATER=1)

RELATIVE DENSITY: 0.86 g/cm³ AT 60°F (15.5°C)

MELTING POINT: N/D

BOILING RANGE: N/D

FREEZING/MELTING POINT: N/D

pH: N/A

OCTANOL/WATER COEFF: N.D.

ODOR THRESHOLD: N/D

VAPOR DENSITY: >1 (AIR =1)

FLAMABILITY: N/D

FLASH POINT: 329°F (165°C) (MINIMUM) CLEVELAND OPEN CUP

FLAMMABLE LIMITS IN AIR: LOWER: N/D UPPER: N/D

AUTO-IGNITION TEMPERATURES: N/D

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal temperatures and pressures. Avoid sparks, or flame.

INCOMPATIBLE MATERIALS: Avoid oxidizing agents.

REACTIVITY: Polymerization is not known to occur under normal temperatures and pressures. Not reactive with water.

HAZARDOUS DECOMPOSITION: None under normal temperatures and pressures. Also see **Section 5:**

HAZARDOUS COMBUSTION PRODUCTS.

11. TOXICOLOGICAL INFORMATION

ROUTES OF EXPOSURE: Skin, Eyes, Ingestion, and Inhalation.

ACUTE EFFECTS; May be harmful if swallowed. May irritate eyes and skin. May cause throat irritation, nausea, vomiting and diarrhea. Aspiration hazard. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

REPEATED DOSE EFFECTS: Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis).

SENSITIZATION: Based on best current information, there is no known human sensitization associated with this product.

MUTAGENICITY: Experimental evidence suggests that this product does not cause mutagenesis.

CARCINOGENICITY: Based on best current information, there is no known carcinogenicity as regulated by OSHA; as categorized by ACGOH A1 or A2 substances; as categorized by IARC Group 1 Group 2A or Group 2B agents as either known carcinogens or substances for which there is limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals.

REPRODUCTIVE TOXICITY: Based on best current information, there is no known reproductive toxicity associated with this product.

TERATOGENICITY: Based on best current information, there is no known teratogenicity associated with this product.

NEUROTOXICITY: High vapor/aerosol concentrations (attainable only at elevated temperatures) may cause central nervous system effects such as dizziness, drowsiness or headaches.

TOXICITY DATA:

Component Analysis – LD50/LC50

Mineral Oil

Dermal LD50 Rabbit >5000 mg/kg

Oral LD50 Rat >5000 mg/kg

Zinc dialkyl dithiophosphate (68649-42-3)

Dermal LD50 Rat >2000 mg/kg

Oral LD50 Rat >2000 mg/kg

12. ECOLOGICAL INFORMATION

ECOTOXICITY: No data available.

PERSISTENCE/DEGRADABILITY – Not readily biodegradable.

BIOACCUMULATIVE POTENTIAL - No information available for this product.

MOBILITY IN ENVIRONMENT – Base oil component(s) – Low solubility and floats; expected to migrate from water to land.

~~CODE 803~~ REVERSE EFFECTS – N/A

OCTANOL/WATER PARTITION COEFFICIENT – N/A

VOLATILE ORGANIC COMPOUNDS - Negligible

AQUATIC RELEASE - Advise authorities if product has entered or may enter watercourses or sewer drains.

13. DISPOSAL INFORMATION

DISPOSAL: Dispose in accordance with federal, state, provincial and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste.

USEPA WASTE CODES: This product, if discarded, is not expected to be a characteristic or listed hazardous waste. If recycled in the USA, it must be managed in accordance with 40 CFR Part 279. Processing, use or contamination by user may change the waste code(s) applicable to the disposal of these products.

14. TRANSPORTATION INFORMATION**DOT****PROPER SHIPPING NAME** Petroleum Lubricating Oil – Not regulated as a hazardous material for Land Transport**HAZARD CLASS:** Not regulated**ID NUMBER:** Not regulated**LABEL REQUIRED:** Not regulated**EMERGENCY RESPONSE GUIDE NUMBER:** Not applicable. Reference North American Emergency Response Guidebook.**IATA:** Not regulated**15. REGULATORY INFORMATION****U.S. Federal Regulations**

United States inventory All components are listed or exempted.
(TSCA 8b)

SARA 302/304

Composition/information on ingredients: No products were found

SARA 311/312

Classification Not Applicable

SARA 313

Form R- Reporting This product does not contain any hazardous ingredients at or above regulated thresholds.
Requirements

Supplier notification This product does not contain any hazardous ingredients at or above regulated thresholds.

State Regulations

Massachusetts None of the components are listed.

New Jersey The following components are listed: Mineral Oil (Untreated and Mildly treated)

Pennsylvania None of the components are listed.

CODE: 803

16. OTHER INFORMATION

DATE ISSUED: April 06, 2015
SUPERSEDES:
REVISION NO.
REVISION INFORMATION: GHS Compliance
SDS #: CODE 803

**LUBENET LUBRICANTS
LLC
6 HORWITH DRIVE
NORTHAMPTON, PA 18067
484-275-7990**

The information on this form is furnished solely for the purpose of compliance with the OSHA Act, and shall not be used for any other purpose. The information herein is given in good faith and is based on data considered accurate. However, no warranty, expressed or implied, is made regarding the accuracy of these data or the results to be obtained from the use thereof. This safety sheet was prepared and is to be used only for this product. If the product is used as a component in another product, this safety sheet information may not be applicable.